

FD12 Visibility Meter

- Measurement range 10 to 50 000 m
- Built-in compensation for different types of precipitation
- Minimum of maintenance needed
- Correct visibility data in any weather conditions

The FD12 forward-scatter visibility meter evaluates the Meteorological Optical Range (MOR) by measuring the scatter of infrared light in air. Typical applications of FD12 are visibility measurement at airports and onboard ships, fog detection and warning for highways, and meteorological observations at remote locations.

FD12 consists of a transmitter, a receiver, and a controller. The simplified mechanical design means minimum disturbance to the sample volume of air. The compact construction and factory set mountings ensure easy installation and eliminate problems with start-up adjustments.

A minimum of maintenance is needed. All hardware from electronic components to optics is field-proven. Anodized aluminium surfaces together with a simple construction make the instrument weather-proof. Depending on the environment, the cleaning of the lenses is necessary only a few times per year; the device features automatic detection of contamination and, consequently, alarm for the need of cleaning.

An extensive set of self diagnostic routines monitors sensor operation continuously. In case of a malfunction, an alarm is immediately generated. The failure can be easily located by enquiring the diagnostics about the sensor status.



The measurement range of FD12 is 10 to 50 000 metres. By utilizing digital techniques in hardware design and signal processing, the device exceeds the performance of other forward-scatter instruments. Fast pulse rate used enables precise recognition of weather conditions. The device has a built-in visibility calculation compensation for snow, fog, rain and sleet. The effects of stray light and severe weather are eliminated resulting in accuracy under all circumstances.

In visibility sensor comparisons, FD12 has proved to determine correct visibility data in weather conditions ranging from clear to fog, to heavy rain and snow conditions.

TECHNICAL DATA

FD12 VISIBILITY METER

MEASUREMENT RANGE

Measurement of MOR 10...50 000 m (32...65,500 ft)

INSTRUMENT CONSISTENCY

Variability between units ± 4 %

OUTPUTS & POWER SUPPLY

Serial interfaces RS-232/485

Analog output 4...20 mA current loop

Power supply 115/230 V ±20 %, 50/60 Hz

Power consumption 30 VA + 100 VA with defrosting heaters

ENVIRONMENTAL

Operating humidity 0...100 % RH

Operating temperature -40...+55 °C

Weight 35 kg with pole mast
20 kg with clamp mountings

Dimensions 210 cm (h) × 160 cm (w)

OPTIONS

Optional display unit Vaisala's DD50 Digital Display

Optional modem 300 baud

Optional fixings Mast mounting clamps
Wall mounting clamps



Internet:
<http://www.vaisala.com>

VAISALA Oyj
PL 26, FIN-00421 Helsinki
FINLAND
Phone: +358 9 894 91
Telefax: +358 9 894 9227
Telex: 122832 vsala fi

VAISALA GmbH
Postfach 540267
D-22502 Hamburg
DEUTSCHLAND
Phone: +49 40 851 763-0
Telefax: +49 40 850 8444

VAISALA (UK) Ltd
Suffolk House
Fordham Road
Newmarket
Suffolk CB8 7AA
UNITED KINGDOM
Phone: +44 1638 674 400
Telefax: +44 1638 674 411

VAISALA TMI Ltd
Vaisala House
349 Bristol Road
Birmingham B5 7SW
UNITED KINGDOM
Phone: +44 121 683 1200
Telefax: +44 121 683 1299

VAISALA SA
3, Parc Ariane
Saint-Quentin-En-Yvelines
F-78284 Guyancourt Cedex
FRANCE
Phone: +33 1 3057 2728
Telefax: +33 1 3096 0858

VAISALA Inc.
100 Commerce Way
Woburn, MA 01801 - 1068
USA
Phone: +1 781 933 4500
Telefax: +1 781 933 8029

VAISALA Inc.
Artais Division
7450 Industrial Parkway
Plain City, OH 43064 - 9005
USA
Phone: +1 614 873 6880
Telefax: +1 614 873 6890

VAISALA KK
42 Kagurazaka 6-Chome
Shinjuku-Ku,
Tokyo 162
JAPAN
Phone: +81 3 3266 9611
Telefax: +81 3 3266 9610

VAISALA Pty. Ltd.
3 Guest Street
Hawthorn, VIC 3122
AUSTRALIA
Phone: +61 3 9818 4200
Telefax: +61 3 9818 4522
A.C.N. 006 500 616

VAISALA Beijing
Representative Office
Room 518, 520
Wangfujing Grand Hotel
No. 57 Wangfujing Street
Beijing 100006
PEOPLE'S REPUBLIC OF
CHINA
Phone: +86 10 6522 4050
Telefax: +86 10 6522 4051