



Features and Benefits

- AeroTRAK™ 9350 particle counter: 0.3 to 25 µm
- AeroTrak™ 9550 particle counter: 0.5 to 25 µm
- Up to six channels of simultaneous data
- 50 L/min flow rate
- Complies with all requirements of ISO 21501-4
- 10,000 sample record storage, 999 locations
- Ethernet and USB outputs
- Industry's loudest audible alarm
- Easy icon-driven touch screen operation
- Reports for ISO-14644-1, EU GMP Annex 1, and FS209E
- Allows storage and recall of specific tests/recipes
- Displays up to three environmental parameters
- Stainless steel enclosure
- Lightweight
- Stand-alone or integrate into a facility monitoring system
- Clean room classification down to ISO Class 2

AEROTRAK™ Portable Particle Counters Models 9350 & 9550

The TSI AEROTRAK™ 9350 and 9550 Portable Particle Counters offer best-in-class features and versatility. They provide a 50 L/min flow with 0.3 or 0.5 µm sensitivity. Perform ISO 14644-1 classifications and complete certifications of EU GMP facilities, by sampling 1 m³ of air in just 20 minutes. Compatible with TSI's accurate ventilation probes that measure air velocity/temperature, these products provide you with a complete solution for your certification needs.

These particle counters can generate pass/fail reports for ISO 14644-1, EU GMP Annex 1, and FS209E. These products can be used as a stand-alone particle counter or integrated into a facility monitoring system like TSI's FMS 5.

Both Models 9350 and 9550 comply with all the stringent requirements set forth in ISO 21501-4. These particle counters are calibrated with NIST traceable PSL spheres using TSI's world-class Classifier and Condensation Particle Counters, the recognized standard for particle measurements. Backed with a standard two-year warranty and TSI's long-standing reputation for high quality, there are no other particle counters like it on the market today.



Specifications

Models 9350 & 9550

AERO^{TRAK}™ Portable Particle Counters

Features	9350 & 9550	
Size Range	9350-02	9550-02
	9350: 0.3 to 25 µm	9550: 0.5 to 25 µm
Particle Channel Sizes	9350-02: 0.3, 0.5, 1.0, 2.0, 3.0, 5.0 µm, additional channel sizes available	9550-02: 0.5, 0.7, 1.0, 3.0, 5.0, 10 µm, additional channel sizes available
	Size Resolution	9350-02: <15% @ 0.5 µm (per ISO 21501-4)
Counting Efficiency	9350-02: 50% at 0.3 µm; 100% for particles >0.45 µm (per ISO 21501-4 and JIS)	9550-02: 50% at 0.5 µm; 100% for particles >0.75 µm (per ISO 21501-4 and JIS)
	Concentration Limit	>250,000/ft ³ at 5% coincidence loss
Light Source	Long life laser diode	
Zero Count	<1 count per 5 minutes (per ISO 21501-4 and JIS B9921)	
Flow Rate	50 L/min (1.77 CFM) ±5% accuracy (meets ISO 21501-4 and JIS B9921)	
Flow Rate Control	Electronic, automatic closed loop (patented* flow control technology)	
Sample Tube Extension	Up to 12 m	
Sampling Modes	Manual, automatic, beep; cumulative/differential; count or concentration	
Sampling Time	1 second to 99 hours	
Sampling Frequency	1 to 9999 cycles or continuous	
Exhaust	Internal HEPA filter	
Vacuum Source	Internal pump	
Communication Mode	Modbus® TCP over Ethernet or USB	
Data Storage	10,000 sample records: includes date, time, six particle channels, flow, ID, and sample volume; transferable via USB data download or TRAKPro™ Lite software	
Audible Alarm	Built-in; >85 dB at 1 meter (adjustable)	
Status Indicators	Low battery, flow, laser	
Alarm Output	Dry contacts, closed when alarm is engaged	
Alarm Limits	Programmable for all particle channels	
Display	VGA 14.5-cm touch screen display	
Languages	English, German, French, Spanish, Japanese, Chinese (simplified), Italian	

Features	9350 & 9550
Software	Compatible with TRAKPro™ Lite and FMS 5 software
Printer	Built-in thermal printer (also available without printer)
Printer Output	Prints in all available languages
Environmental Sensor Interface	Supports TSI Probe Models: 960, 962, 964, 966 (air velocity/temp/RH) and Temp/RH probe
Unit ID	Configurable IP address
Security	2-level password protection to lock out usage and configuration
Location ID	Up to 999 Locations; 16 characters long
Reports	Provides Pass/Fail on ISO 14644-1, EU GMP, and FS209E reports
Calibration	NIST traceable using TSI calibration system
Calibration Frequency	Recommended minimum of once per year
Dimension (H x W x D)	24.1 cm x 23.0 cm x 23.2 cm (without isokinetic inlet)
Weight	6.44 kg with two batteries
Power	110 to 240 VAC universal power supply
Battery	Removable/rechargeable Li-Ion batteries (2 battery slots)
Battery Life	>3 hours of continuous operation
Battery Recharge	4 hours (when idle)
External Surface	Stainless steel
Operating Range	5° to 35°C, 20% to 95% noncondensing
Storage Range	0° to 50°C, up to 98% RH noncondensing
Standards	ISO 21501-4, CE, JIS B9921
Warranty	Two years, extended warranties available
Included Accessories	Printed QuickStart guide, operating manual on CD, power supply, battery, barbed inlet, isokinetic probe, tripod, tubing, purge filter, printer paper, USB cable, and TRAKPro™ Lite software
Optional Accessories	Electronic filter scanning probe, basic filter scanning probe, TSI velocity probes, Temp/RH probe, additional battery, dual port external battery charger, isokinetic probes, isokinetic inlets, sample tubing, carrying case

*Patent Number 6,167,107

Specifications are subject to change without notice. TSI, the TSI logo, AERO^{TRAK}, and TRAK^{PRO} are trademarks of TSI Incorporated. Modbus is a registered trademark of Modicon, Inc.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA	Tel: +1 800 874 2811	E-mail: info@tsi.com	Website: www.tsi.com
UK	Tel: +44 149 4 459200	E-mail: tsiuk@tsi.com	Website: www.tsiinc.co.uk
France	Tel: +33 491 11 87 64	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
Germany	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
India	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
China	Tel: +86 10 8251 6588	E-mail: tsibeijing@tsi.com	
Singapore	Tel: +65 6595 6388	E-mail: tsi-singapore@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.