

HMD42/53 Humidity and Temperature Transmitters for Ducts in Commercial HVAC Applications



Features/Benefits

- Designed for building automation applications
- ± 3 %RH accuracy
- Full 0 ... 100 %RH measurement range
- $-20 \dots +60$ °C ($-4 \dots +140$ °F) operating range
- IP65 (NEMA 4) metal housing
- Excellent stability and high reliability
- Fully interchangeable Vaisala INTERCAP® Sensor
- Variety of analog signal outputs available

The duct mounted Vaisala INTERCAP® Humidity and Temperature Transmitters HMD42 and HMD53 are designed for building automation applications. They combine reliable operation with excellent stability, providing low cost of ownership to the user.

Flexibility in Humidity and Temperature Measurement

The HMD42/53 transmitters measure humidity with a ± 3 %RH accuracy and temperature with a ± 0.4 °C (± 0.72 °F) accuracy. They feature various selectable analog output signals and they can be powered by either AC or DC voltage.

Easy Maintenance

The HMD42/53 humidity transmitters use Vaisala INTERCAP® Sensor - the interchangeable capacitive humidity sensor. The transmitters require no recalibration if the sensor is changed. This means great savings in overall maintenance costs.

Reliable Performance in Harsh Environments

The duct mount HMD42/53 transmitters can be installed in various measurement environments due to the robust IP65 (NEMA4) rated metal enclosure, which protects the sensor from dust and splashes of water. The wide measurement temperature range from -20 °C to $+60$ °C ($-4 \dots +140$ °F) covers most HVAC applications.

Typical Applications

- Office buildings
- Retail spaces
- Governmental buildings
- Educational facilities
- Sport and event complexes
- Hotels and conference centers
- Airports
- Metro stations

Technical Data

Relative Humidity

| | | |
|--|---|--|
| Measurement range | 0 ... 100 %RH | |
| Typical accuracy | | |
| Temperature range | 0 ... +40 °C (+32 ... +104 °F) | |
| 0 ... 90 %RH | ±3 %RH | |
| 90 ... 100 %RH | ±5 %RH | |
| Temperature range | -20 ... 0 °C, +40 ... +60 °C (-4 ... +32 °F, +104 ... +140 °F) | |
| 0 ... 90 %RH | ±5 %RH | |
| 90 ... 100 %RH | ±7 %RH | |
| Humidity sensor | Vaisala INTERCAP® | |
| Stability | ±2 %RH / 2 years | |
| Response time at 20 °C (+68 °F), 90 % response | 15 s | |

Temperature

| | | |
|---|----------------------------------|--|
| Measurement range | -20 ... +60 °C (-4 ... +140 °F) | |
| Output scale | -40 ... +60 °C (-40 ... +140 °F) | |
| Accuracy | | |
| 0 ... +40 °C (+32 ... +104 °F) | ±0.4 °C (±0.72 °F) | |
| -20 ... 0 °C, +40 ... +60 °C (-4 ... +32 °F, +104 ... +140 °F) | ±0.6 °C (±1.1 °F) | |
| Sensor | Pt1000 IEC 751 Class B | |

General - HMD42

| | | |
|----------------|----------------------------------|--|
| Supply voltage | 10 ... 35 VDC ($R_L = 0$ ohm) | |
| | 20 ... 35 VDC ($R_L = 500$ ohm) | |
| Output signal | 4 ... 20mA | |

General - HMD53

| | | |
|--|--------------|------------|
| Supply voltage range depends on the selected output signal | | |
| | DC | AC |
| 0 ... 1V | 10 ... 35V | 9 ... 24V |
| 0 ... 5V | 14 ... 35V | 12 ... 24V |
| 0 ... 10V | 19 ... 35V | 16 ... 24V |
| WITH OPTIONAL CURRENT MODULE | | |
| 0 ... 20 mA ($R_L = 0$ ohm) | 10 ... 35V | 11 ... 24V |
| **0 ... 20 mA ($R_L = 500$ ohm) | 20 ... 35V | 17 ... 24V |
| Power consumption @ 24VAC | 12mA typical | |

**Optional temperature scales are available on request.

General

| | | |
|--|--|--|
| Operating temperature range | | |
| electronics | -5 ... +55 °C (+23 ... +131 °F) | |
| probe | -20 ... +60 °C (-4 ... +140 °F) | |
| Storage temperature range | -40 ... +60 °C (-40 ... +140 °F) | |
| Maximum flow speed | 50 m/s | |
| Housing material | | |
| probe | stainless steel | |
| electronics | cast aluminium | |
| Housing classification | IP65 (NEMA 4) | |
| Connections | screw terminal 0.5 ... 1.5 mm ² | |
| Cable thread-through bushing for 7 ... 10 mm (PG9) included | (18941HM) | |
| Complies with EMC standard EN61326 and EN55022 | | |

Accessories



| | |
|----------------------------|---------|
| Armoured cable gland | 10528HM |
| Current module (for HMD53) | 18945HM |

Spare Parts

| | |
|----------------------------------|-------------------|
| Vaisala INTERCAP sensor, 1 piece | 15778HM |
| Vaisala INTERCAP sensor, 10 pcs | INTERCAPSET-10PCS |
| Membrane filter | DRW010525 |
| Sintered filter | HM46670SP |

Dimensions

Dimensions in mm



VAISALA

For more information, visit
www.vaisala.com or contact
 us at sales@vaisala.com

Ref. B211140EN-A ©Vaisala 2011

This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications — technical included — are subject to change without notice.

